



SPECIFICATIONS

MODELS	Normal length	Bending force	WORK AREA						TECHNICAL SPECIFICATIONS					DIMENSIONS AND WEIGHT				
			Max real length	Distance side frames	Throat	Y stroke	Daylight	Working table height	Approaching speed	Working speed	Return speed	Power 60Hz-480 V	Oil tank capacity	Length	Height (H for transport)	Depth	Pit depth	Approximate weight
	inch	US Ton	inch	inch	inch	inch	inch	inch	inch/s	inch/s	inch/s	kW	Gal	inch	mm	inch	inch	lbs
40/44	49.21	44	49.21	47.24	0	7.87	15.75	39.17	9.84	0-0.4	9.84	4	13.2	78.74	2200	53.15	0	11,025
	62.99	55	65.75	51.18	11.81	7.87	15.75	37.40	7.87	0-0.4	7.87	5.5	10.5	104.33	2550 (2475)	63.39	0	12,786
50/55	78.74	55	82.68	62.99	11.81	7.87	15.75	37.40	7.87	0-0.4	7.87	5.5	10.5	116.14	2550 (2475)	63.39	0	13,670
	98.43	122	102.36	82.68	15.75	11.81	19.69	37.40	7.87	0-0.4	7.87	11	26.5	136.81	3030 (2830)	78.74	0	23,150
110/122	118.11	122	122.05	102.36	15.75	11.81	19.69	37.40	7.87	0-0.4	7.87	11	26.5	157.48	3030 (2830)	78.74	0	26,450
	157.48	122	161.42	141.73	15.75	11.81	19.69	37.40	7.87	0-0.4	7.09	11	26.5	196.85	3030 (2830)	78.74	0	31,550
	196.85	122	200.79	181.10	15.75	11.81	19.69	37.40	7.09	0-0.4	6.30	11	26.5	235.24	3030 (2830)	78.74	0	36,600
	236.22	122	240.16	220.47	19.69	11.81	19.69	42.32	5.91	0-0.4	5.12	11	26.5	275.59	3030 (2830)	78.74	0	39,465
	98.43	190	102.36	82.68	19.69	11.81	19.69	37.40	7.87	0-0.4	7.87	18.5	40	136.81	3140 (2970)	78.74	0	26,455
170/190	118.11	190	122.05	102.36	19.69	11.81	19.69	37.40	7.87	0-0.4	7.87	18.5	40	157.48	3140 (2970)	84.65	0	31,085
	157.48	190	161.42	141.73	19.69	11.81	19.69	37.40	7.87	0-0.4	7.87	18.5	40	196.85	3140 (2970)	84.65	0	37,480
	196.85	190	200.79	181.10	19.69	11.81	19.69	37.40	7.09	0-0.4	7.09	18.5	40	236.22	3140 (2970)	84.65	0	45,635
	236.22	190	240.16	220.47	19.69	11.81	19.69	42.32	7.09	0-0.4	7.09	18.5	40	275.59	3140 (2970)	84.65	0	52,910
	118.11	275	122.05	102.36	19.69	11.81	19.69	37.99	7.87	0-0.4	7.09	22	74	158.27	3340 (3260)	82.68	0	39,905
250/275	157.48	275	161.42	141.73	19.69	11.81	19.69	37.99	7.87	0-0.4	7.09	22	74	197.64	3410 (3260)	82.68	0	48,500
	196.85	275	200.79	181.10	19.69	11.81	19.69	38.78	7.09	0-0.4	7.09	22	74	240.16	3700	86.61	0	64,000
	236.22	275	240.16	220.47	19.69	11.81	19.69	42.32	7.09	0-0.4	7.09	22	74	276.38	3800 (3500)	90.55	0	77,165
320/355	118.11	355	122.05	102.36	19.69	13.78	22.83	37.99	7.09	0-0.4	7.09	30	74	159.06	3650 (3600)	94.49	0	45,195
	157.48	355	161.42	141.73	19.69	13.78	22.83	37.99	7.09	0-0.4	7.09	30	74	198.43	3650 (3600)	94.49	0	53,000
	196.85	355	200.79	181.10	19.69	13.78	22.83	37.99	5.91	0-0.4	5.51	30	74	247.05	3850 (3800)	94.49	0	67,700
	236.22	355	240.16	220.47	19.69	13.78	22.83	37.99	5.91	0-0.4	5.51	30	74	277.17	4050 (4000)	94.49	27.5	81,600

COMEQ.COM

YOUR SOURCE FOR METAL
FABRICATING MACHINERY SINCE 1972

10521 INDUSTRIAL PARK RD,
WHITE MARSH, MD 21162

P: 410.933.1600
sales@comeq.com



PRIMELINE BY VICLA



PRIMELINE

By **VICLA**

CNC HYDRAULIC PRESS BRAKES

HEAVY-DUTY, FAST, EXACT, PRODUCTIVE, SAFE

- Set your bend and be sure to achieve it – fast and spot-on every single time
- Hydraulic Crowning System managed by the CNC
- Hybrid System (energy savings up to 55% compared to a conventional hydraulic machine)
- Voith Pump and Hoerbiger hydraulic system
- High efficiency motor – class IE3
- Double-guided RAM
- Parallel frames to guarantee precision and high speed of the backgauge movements
- ESA or DELEM control

- IRIS by Lazersafe, ZERO distance speed change with optional angle control
- American tooling or Promecam, WILA New Standard Pro or Premium options
- CLEVER CROWNING: the option for real time corrections at each bend
- FLEX - innovative optional system to ensure same bending depth regardless of the length of the bend
- Configured to your application needs

Produced & Assembled in Italy 



SMART SERIES

ACCURATE, RUGGED, RELIABLE, USER FRIENDLY, COMPETITIVE

- The clever choice for all your forming application needs
- Hydraulic Crowning System managed by the CNC
- ESA or DELEM control
- IRIS by Lazersafe, ZERO distance speed change with optional angle control
- American tooling or Promecam, WILA New Standard Pro or Premium options
- Dedicated automation solutions available
- Configured to your application needs

Produced & Assembled in Italy 

INNOVATION THAT INCORPORATES THE LATEST ADVANCEMENTS IN PRECISION PRESS BRAKE TECHNOLOGY

ENGINEERED TO ACTIVELY RESPOND TO MECHANICAL STRESSES THROUGH A "HYDRAULIC CROWNING" SYSTEM